

TP-Link Omada AC1200 Wireless Wall-Plate Access



Code:
WAPTP4824152

Vendor code:
EAP225-WALL

EAN code:
6935364099794

802.11n/g/b/ac, 2.4GHz 2 x 3dBi, 5GHz 2 x 4dBi, 9W

Complete In Room Wi-Fi Coverage

An EAP in each room guarantees a strong wireless signal and allows guests to enjoy their own private Wi-Fi network.

Effortless Deployment and Scalability

With 802.3af/802.3at Power over Ethernet supported there's no need to install additional wiring in the building. Simply plug in existing Ethernet cables and you're ready to go.

Installation Made Easy

Upgrade Ethernet wall jacks to high-performance Wi-Fi access points. The EAPs can be fitted to existing EU or US wall junction boxes, making installation quick and non-disruptive.

Three Ethernet Jacks, One PoE Outlet

More than just a wireless access point, EAP225-Wall acts as a switch and provides three standard Ethernet jacks together with a Power over Ethernet outlet, capable of powering wired devices such as IP phones, IP cameras,

intercoms and more.

Blends Into Your Wall

The EAP225-Wall wireless access point blends into any business setting with a refined, minimalist appearance.

Gigabit Wi-Fi Speeds with MU-MIMO Technology

EAP225-Wall delivers combined dual-band speeds of up to 1200Mbps. Armed with the latest 802.11ac Wave 2 MU-MIMO technology, it can exchange data with multiple clients at the same time to allow more devices to connect without any slowdown to the network.- AC1200 wireless with 100Mbps Ethernet backhaul- Designed for office cubical and hotel room wired and wireless connections- Easy-mount construction allows installation into 1-gang electric wall-box- Compact, low-profile design fits discreetly with any existing interior style- Free cloud management and Omada App supported for ultra convenience and easy management- Power over Ethernet (802.3af/802.3at) support makes deployment effortless and flexible- Enterprise-class Wi-Fi security helps to decrease network security threats- Supports management VLAN for an enhanced network management

Antenne

Antennas quantity	2
Geïntegreerde antenne	Ja
Versterking antenne (max)	4 dBi

Beveiliging

MAC adres filtering	Ja
Ondersteunde beveiligingsalgoritmen	64-bit WEP, 128-bit WEP, 152-bit WEP, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK

Design

Intern	Ja
Kleur van het product	Wit
Plaatsing	Muur

Eisen aan de omgeving

Luchtvochtigheid bij opslag	5 - 90 procent
Relatieve luchtvochtigheid, in bedrijf	0 - 40 procent
Temperatuur bij opslag	-40 - 70 °C
Temperatuur, in bedrijf	10 - 90 °C

Energie

Power over Ethernet (PoE)	Ja
Typisch stroomverbruik	9 W
Vermogensverbruik (max)	25,5 W

Gewicht en omvang

Breedte	86 mm
Diepte	19,7 mm
Hoogte	143 mm

Inhoud van de verpakking

Aantal inbegrepen producten	1 stuk(s)
Inclusief AC-adapter	Ja
Montage gereedschap	Ja
Snelstartgids	Ja

Poorten & interfaces

Aantal Ethernet LAN (RJ-45)-poorten	3
-------------------------------------	---

Prestatie

2,4 GHz	Ja
5 GHz	Ja
Automatische kanaalselectie	Ja
Certificering	FCC, RoHS
Ethernet LAN, data-overdrachtsnelheden	10,1000 Mbit/s
MIMO	Ja
MIMO-type	Multi User MIMO
Netwerkstandaard	IEEE 802.11b,IEEE 802.11g,IEEE 802.11n,IEEE 802.3ac
Overdrachtssnelheid (max)	1200 Mbit/s
Quality of Service (QoS)	Ja
Rate limiting	Ja
Reset button	Ja
Web-gebaseerd management	Ja