

TP-Link Omada Cloud Controller



Code:
WAPTP4865711

Vendor code:
OC200

EAN code:
6935364084233

OC200 Omada, 10/100Mbps LAN, USB 2.0, Micro USB, PoE, 100×98×25 mm

Dedicated In Network Centralized Management

The OC200 Omada Cloud Controller is delicate to provide centralized management for the whole Omada network. Monitor statistics in real-time, view a graphical analysis of network traffic, create a captive portal, upgrade and reboot your system, and easily scale your network to boost your business.

Free Cloud Management – Anywhere, Anytime

Omada offers free cloud access to its centralized management platform. Take your network with you, wherever you go.

Industry Leading Hardware Design

Equipped with an advanced hardware design and the latest chipset, OC200 has the impressive processing power to support the massive management of your business network.

Guest Network with Facebook Wi-Fi and SMS Login

Visitors have access to secure Wi-Fi with captive portal and wireless isolation technology. Newly added SMS

authentication simplifies the connection process, while Facebook authentication raises the social media profile of your business.

Even More Convenient with Omada App

Remotely access and configure the OC200 from the convenience of your smartphone, wherever you are in the world.- Omada Wi-Fi network controller- Accessible through direct access, cloud portal or mobile app- Pre-installed Omada controller software. Power it on and start to play- No license fee, no monthly fee, manage from anywhere, anytime- Dual power selection PoE (802.3af/802.3at) and micro USB flexible installations- Powerful CPU and USB auto backup for robustness and stability- Secure guest network with multiple login options(Facebook Wi-Fi, SMS login, Voucher)

Beeldscherm

Besturings -en afbeeldingseenheid	Nee
-----------------------------------	-----

Beheerfuncties

Quality of Service (QoS)	Ja
Reset button	Ja
Web-gebaseerd management	Ja

Beveiliging

MAC adres filtering	Ja
Ondersteunde beveiligingsalgoritmen	SSID,WEP,WPA,WPA-PSK,WPA2,WPA2-PSK
VLAN=ondersteuning	Ja

Certificaten

Certificering	CE, FCC, RoHS
---------------	---------------

Eisen aan de omgeving

Luchtvochtigheid bij opslag	5 - 90 procent
Relatieve luchtvochtigheid, in bedrijf	10 - 90 procent
Temperatuur bij opslag	-40 - 70 °C
Temperatuur, in bedrijf	0 - 40 °C

Energie

Power over Ethernet (PoE)	Ja
Typisch stroomverbruik	5 W

Geheugen

Flash memory	4000 MB
Intern geheugen	1024 MB

Intern geheugentype

DDR3

Gewicht en omvang

Breedte	100 mm
Diepte	98 mm
Hoogte	25 mm

Indicatie

LED-indicatoren	Ja
-----------------	----

Inhoud van de verpakking

Meegeleverde kabels	LAN (RJ-45)
Snelle installatiehandleiding	Ja

Netwerk

Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s
Netwerkstandaard	IEEE 802.3af,IEEE 802.3at

Poorten & interfaces

Aantal Ethernet LAN (RJ-45)-poorten	2
Aantal USB 2.0-poorten	1

Software

Compatibele besturingssystemen	Windows10, 8, 7,Vista, XP; MAC OS; NetWare, UNIX; Linux
--------------------------------	---

Technische details

Aantal geïnstalleerde processoren	1
Frequentie van processor	1000 MHz
Type processor	Ja